

SPECIFICATION

Surface Mounted Large Capacity Waste Receptacle shall hold 17 gallons [64 liters]. Unit shall be 22 gauge type 304 stainless steel alloy 18-8 with satin finish and be protected during shipment with a PVC film easily removable after installation. Receptacle shall have no exposed fastening devices or spot welded seams and have front vertical edges rounded to 1/2" [13] radius. Receptacle shall have four (4) interior hooks for hanging a reusable heavy gauge vinyl liner bag with grommets (to order replacements specify model 25-PY). Receptacle shall be screw mounted to wall through keyhole slots on back of unit and shall be theft resistant after installation of concealed locking screw.

Surface Mounted Large Capacity Waste Receptacle shall be Model № 0825 as manufactured by American Specialties, Inc., 441 Saw Mill River Road, Yonkers, New York 10701-4913

INSTALLATION

For general utility, mount the receptacle 16" [406] above finished floor (AFF) from bottom of unit. Hang unit on preinstalled four (4) screws (by others) on wall through the mounting keyhole slots. Install and fasten theft-resistant screw (by others) to wall through top middle hole of receptacle.

OPERATION

User deposits waste material. Maintenance schedule determines trash removal cycle. Unit is emptied by removing either disposable bag (supplied by others) or reusable liner bag (available separately) to empty into appropriate bulk collection container. Liner bag is washable and reusable and replacements are available should they be required (specify model 25-PY).

Acc	cessory Specialties	AMERICAN DISPENSER	Desert Ray Products	WATROUS.MC.	
BERL'S COMMERCIAL	BERLS.CON	1 (704) 937-2673		Drive, Unit A, Mooresville, NC 281	15