



**Model 6324 *Bradex*<sup>®</sup>**

- Lavatory-Mounted
- Pump-Type Valve
- 4" Spout, 4<sup>3</sup>/<sub>4</sub>" Shank
- ADA Compliant

**Product Materials**

- PLUNGER AND SPOUT:** stainless steel. Requires less than 5 lbs. of force to activate plunger.
- ESCUTCHEON:** heavy chrome-plated brass.
- SHANK:** molded ABS plastic.
- VALVE CYLINDER:** molded clear ABS plastic.
- VALVE COMPONENTS:** Celcon, Buna-N rubber or stainless steel.
- PLASTIC GLOBE:** translucent polyethylene.

**Operation**

Depress piston for measured amount of liquid soap. Fills from top by unlocking and withdrawing piston and spout assembly using special wrench provided. Model 6324 will dispense vegetable or coconut oil liquid soaps, synthetic detergents, and antiseptic solutions in a liquid form. Spout is fixed. Requires less than 5 lbs. force to activate plunger.

- Bradley liquid soap valves operate best with any vegetable oil or coconut oil hand soap having a 10–15% soap concentration.

**Installation**

Verify all rough-in dimensions prior to installation. Mount dispenser in 1" diameter hole in lavatory or counter-top. Include dispenser mounting hole location in lavatory specifications or mount in unused faucet hole. Shank will accommodate a maximum 3<sup>1</sup>/<sub>2</sub>" mounting thickness and can be cut in the field.

**Optional Features**

Feature	Suffix
<input type="checkbox"/> Plastic globe 32 oz.*	-68
* <b>Bradex</b> <sup>®</sup>	

**Guide Specification**

Lavatory-mounted liquid soap dispenser manufactured of stainless steel, chrome-plated brass and molded ABS plastic. Buna-N O-ring seals and duckbills. Valve shall dispense measured amount of vegetable or coconut oil liquid soap, synthetic detergents, or antiseptic solutions. Servicing is facilitated by use of special wrench. Requires less than 5 lbs. of force to activate plunger.

Orders composed of products indicated as **Bradex**<sup>®</sup> will be available to ship in three days after receipt of order at the factory. There is no pricing penalty for this service from Bradley.

Page 1 of 1  
 4/14/2017  
 This information is subject to change without notice.  
 Bradley\_SoapDispenser\_6324

The technical drawing shows a side view of the soap dispenser with the following dimensions: Spout length is 4" (102mm). The distance from the top of the globe to the top of the valve is 2<sup>3</sup>/<sub>4</sub>" (70mm). The maximum mounting thickness is 3<sup>1</sup>/<sub>2</sub>". The diameter of the mounting hole is 2" (51mm). The diameter of the valve cylinder is 1<sup>3</sup>/<sub>16</sub>" (21 mm). The overall height of the globe is A" and the diameter of the globe is B". An ADA compliant logo is also present.

DIMENSIONS			
Model	A	B	Capacity
6324*	7 <sup>1</sup> / <sub>8</sub> " (181mm)	2 <sup>1</sup> / <sub>2</sub> " (64mm)	16 oz.
6324-68*	8 <sup>1</sup> / <sub>16</sub> " (227mm)	3 <sup>1</sup> / <sub>4</sub> " (83mm)	32 oz.
* <b>Bradex</b> <sup>®</sup>			

**ADA Compliant**

- Consult local and national accessibility codes for proper installation guidelines.
- Conformity and compliance to local and national codes is the responsibility of the installer.

© 2017 Bradley  
 P.O. Box 309, Menomonee Falls, WI 53052-0309  
 800 BRADLEY (800 272 3539) +1 262 251 6000  
 bradleycorp.com