

XLERATOReco[®] HAND DRYER



500 WATTS. 12 SECONDS. NO HEAT.

THE MOST ENERGY-EFFICIENT, ENVIRONMENTALLY FRIENDLY HAND DRYER ON THE PLANET



Distributed By



RESTROOMDIRECT
COMMERCIAL RESTROOM ACCESSORIES

WWW.RESTROOMDIRECT.COM

704-937-2673

129 Oak Park Dr., Unit A, Mooresville, NC 28115

XLERATOR^{eco}® HAND DRYER



MODELS: **XL - BW** **W** **GR** **C** **SB** **SI** **SP** - **ECO** OPTIONS: **-1.1N** (Noise Reduction Nozzle) **-H** (HEPA Filter) **-VOLTAGE** (See Chart)



XL-BW-ECO
White Thermoset Resin (BMC)

FEATURES & BENEFITS

- ✓ New No Heat Technology
- ✓ 12 Second Dry Time*
- ✓ 500 Watts
- ✓ Adjustable Speed and Sound Control
- ✓ Can Install Multiple XLERATOReco Units On One Circuit
- ✓ 95% Cost Savings Vs. Paper Towels
- ✓ 5-Year Limited Warranty
- ✓ Made In USA Certified®
- ✓ GreenSpec® Listed and Helps Qualify for several LEED® credits
- ✓ Virtually Maintenance Free

OPTIONS

- ✓ **HEPA Filtration System:** Filters 99.97% of bacteria at 0.3 microns from the air stream.
- ✓ **1.1 Noise Reduction Nozzle:** Lowers decibel level 9 dB by reducing air deflection noise but increases dry time by approximately 3 seconds.

ONLINE INFORMATION

- ▶ Product Videos
- 💰 Cost Savings & Carbon Footprint Calculator
- 📊 Life Cycle Assessment Study
- 📄 Case Studies
- 📋 3 Part Specifications
- 👁️ CAD/BIM Images
- 📖 AIA/GBCI CEU Courses
- 📄 Technical Data Sheet



XL-W-ECO
White Epoxy Painted



XL-GR-ECO
Graphite Textured Painted



XL-SP-ECO**
Custom Special Paint



XL-SI-ECO***
Custom Special Image



XL-C-ECO
Chrome Plated



XL-SB-ECO
Brushed Stainless Steel

DIMENSIONS

Width 11 3/4" (298 mm) **Height** 12 11/16" (322 mm) **Depth** 6 11/16" (170 mm)

WEIGHT

XL-BW-ECO: 15 lbs. (6.8 kgs.) **XL-SB-ECO:** 16 lbs. (7.26 kgs.)
XL-W-ECO, XL-GR-ECO, XL-C-ECO, XL-SI-ECO, XL-SP-ECO: 17 lbs. (7.71 kgs.)

ELECTRICAL

VOLTS	AMPS	WATTS	HERTZ	
110-120V	4.3-4.5A	460-530W	50/60 Hz	UL US
208-277V	2.2-2.2A	425-500W	50/60 Hz	UL US
230V	2.2A	500W	50 Hz	CE

NOTE: Drawing 4.5 Amps or less allows for the installation of multiple XLERATOReco units on one circuit, significantly reducing installation costs and creating a return on investment of less than one year.

ACTIVATION

Automatic Sensor Operated

MOUNTING

Surface Mounted

SUGGESTED MOUNTING HEIGHTS

Men 45" (114 cm) **Women** 43" (109 cm) **Handicapped** 37" (94 cm)

Note: Heights measured from floor to bottom of dryer.

ACCESSORIES

- ✓ Anti-Microbial Wall Guards
- ✓ XChanger Paper Towel Dispenser Retrofit Kit
- ✓ ADA-Compliant Recess Kit



Width 16 3/8" (416 mm) **Height** 26" (660 mm)
Depth 3 3/8" (86 mm) **Weight** 11 lbs. (4.99 kgs.)

Part # 40502



RoHS



* Dry time based on third party testing performed by SGS International on standard XLERATOReco® hand dryer with 0.8" nozzle to 0.2g or less of residual moisture.
** Special Paint powder-coated covers are available in many colors and textures.
*** Exclusive digital image technology allows for the addition of company, school or team logos with any color, design or a 'green message'.



TIME TO THROW IN THE TOWEL®

EXCEL DRYER INC • 1.800.255.9235 • EXCELDRIYER.COM

DECEMBER
2015