



Model 6326 — Bradex®

- Lavatory-Mounted
- Pump-Type Valve
- 6" Spout
- ADA Compliant

Product Materials

- PLUNGER AND SPOUT:** stainless steel. Requires less than 5 lbs. of force to activate plunger.
- ESCUTCHEON:** heavy chrome-plated brass.
- SHANK:** molded ABS plastic.
- VALVE CYLINDER:** molded clear ABS plastic.
- VALVE COMPONENTS:** Celcon, Buna-N rubber or stainless steel.
- PLASTIC GLOBE:** translucent polyethylene.

Operation

Depress piston for measured amount of liquid soap. Fills from top by unlocking and withdrawing piston and spout assembly using special wrench provided. The 6326 will dispense vegetable or coconut oil liquid soaps, synthetic detergents, and antiseptic solutions in a liquid form. Spout is fixed. Requires less than 5 lbs. of force to activate plunger.

- Bradley liquid soap valves operate best with any vegetable oil or coconut oil hand soap having a 10–15% soap concentration.

Installation

Verify all rough-in dimensions prior to installation. Mount dispenser in 1" diameter hole in lavatory or counter-top. Include dispenser mounting hole location in lavatory specifications or mount in unused faucet hole. Shank will accommodate a maximum 3½" mounting thickness and can be cut in the field.

Optional Features

Feature	Suffix
<input type="checkbox"/> Plastic globe 32 oz.*	-68

* **Bradex®**

Guide Specification

Lavatory-mounted liquid soap dispenser manufactured of stainless steel, chrome plated brass and molded ABS plastic. Buna-N O-ring seals and duckbills. Valve shall dispense measured amount of vegetable or coconut oil liquid soap, synthetic detergents, or antiseptic solutions. Servicing is facilitated by use of special wrench. Requires less than 5 lbs. of force to activate plunger.

Orders composed of products indicated as **Bradex®** will be available to ship in three days after receipt of order at the factory. There is no pricing penalty for this service from Bradley.

Page 1 of 1
4/14/2017
This information is subject to change without notice.
Bradley_SoapDispenser_6326

The diagram shows a side view of the soap dispenser with the following dimensions: Spout length is 6" (152mm). The distance from the top of the valve to the start of the spout is 2¾" (70mm). The maximum mounting thickness is 3½". The diameter of the mounting hole is 2" (51mm). The diameter of the valve stem is 1³⁄₁₆" (21 mm). The overall height of the dispenser is labeled as 'A" and the diameter of the base is labeled as 'B"'. A photo of the dispenser is shown to the left of the diagram. An ADA Compliant logo is in the top right corner.

DIMENSIONS			
Model	A	B	Capacity
6326*	7½" (181mm)	2½" (64mm)	16 oz.
6326-68*	8¹⁵⁄₁₆" (227mm)	¾" (83mm)	32 oz.

* **Bradex®**

ADA Compliant

- Consult local and national accessibility codes for proper installation guidelines.
- Conformity and compliance to local and national codes is the responsibility of the installer.

© 2017 Bradley
P.O. Box 309, Menomonee Falls, WI 53052-0309
800 BRADLEY (800 272 3539) +1 262 251 6000
bradleycorp.com