# ThinAir® HAND DRYER



# SURFACE MOUNTED. ADA COMPLIANT.

## **NEW ENHANCED STANDARD FEATURES**



Adjustable Speed and Sound Control



Multi-Voltage Options: 110-120V Or 208-277V



Adjustable Heat Settings -High, Medium, Low & Off



Service LED

SECONDS<sup>1</sup> dry time

95% **COST SAVINGS** versus paper towels

80% **LESS ENERGY** than conventional dryers







# ThinAir® HAND DRYER

MODELS: TA - ABS W GR SB SI SB-SI SP -H (HEPA Filter) -VOLTAGE (See Chart)





TA-ABS

White Polymer (ABS)
With SanaFor™ Antimicrobial Additive









# DRY TIME: 14 SECONDS<sup>1</sup>

# **ENERGY PER USE: 3.7 Wh<sup>1</sup>**



UL Environment published the first global Product Category Rules (PCR) for hand dryers which outlined industry consensus testing procedures to quantify environmental impact and performance. Third-party testing to these guidelines documents a product's environmental impact over its lifecycle. This impact is detailed in certified, internationally-recognized Environmental Product Declarations (EPDs). EPDs enable specifiers and buyers to make true apples-to-apples comparisons and more informed product selections. Excel Dryer received the industry's first certified EPDs.

#### **FEATURES & BENEFITS**

Electrostatic HEPA Filtration System: Removes 99.999% of viruses and 99.97% of potentially present bacteria<sup>2</sup> at 0.3 microns from the airstream.

Meets 4" ADA protrusion guidelines when surface mounted

95% Cost Savings Vs. Paper Towels

✓ Made In USA Certified®

5-Year Limited Warranty

BuildingGreen Approved and Helps Qualify for several LEED® credits

A Hygienic Hand Drying Solution

#### **OPTIONAL ACCESSORIES**

Antimicrobial Wall Guards:

• 89W Microban® Wall Guard - White • 89B Microban Wall Guard - Black • 89S Wall Guard - Brushed Stainless Steel



TA-W White Epoxy Painted



TA-GR Graphite Textured



Custom Special Paint



TA-SI<sup>3</sup> Custom Special Image



**TA-SB**Brushed
Stainless Steel



TA-SB-SI<sup>3</sup>
Brushed Stainless
Steel Special Image

## **OVERALL DIMENSIONS**

**Width:** 9 5/32" (233 mm) **Height:** 13 15/16" (354 mm) **Depth:** 3 15/16" (100 mm)

#### **HEPA FILTER DIMENSIONS**

Width: 6.5" (165.6 mm) Height: 3.56" (90.5 mm) Depth: 1.96" (50.0 mm)

#### **PERFORMANCE**

 ADJ. SOUND LEVEL:
 69 - 73 dB
 ADJ. VELOCITY:
 12,000 - 17,000 LFM

 ADJ. HEAT RANGE:
 95°F - 136°F
 ADJ. FLOW RATE:
 29 - 42 CFM

## **ELECTRICAL**

Units are Single Phase; 950 Watts or as low as 300 Watts (without heat) and available as specified in:

VOLTS	AMPS	WATTS	AMPS (NO HEAT)	WATTS (NO HEAT)	HERTZ	LISTING
110-120V	7.0-7.8A	750-920W	2.9-3.4A	300-380W	50/60 Hz	c(UL)us
208-240V	3.8-4.1A	750-950W	1.7-1.9A	330-415W	50/60 Hz	c(UL)us
208-277V	3.8-4.1A	750-950W	1.7-1.9A	330-415W	50/60 Hz	(l)
230V	4.0A	920W	1.9A	415W	50-60 Hz	Œ

# **CERTIFICATIONS**











Building Green

RoHS



#### WEIGHT

TA-ABS: 8 lbs. (3.6 kgs.)

**TA-W, TA-GR, TA-SP, TA-SI, TA-SB, TA-SB-SI**: 10 lbs. (4.5 kgs.)

#### **ACTIVATION**

Automatic Sensor Activated

# MOUNTING

Surface-Mounted

#### **ADA COMPLIANCE**

ADA guidelines state that fixtures mounted above 27" must not protrude more than 4" from the wall.

4"





Maximum: 48" Recommended: 37"

# SUGGESTED MOUNTING HEIGHTS

from floor to bottom of dryer:

Men	45"	(114 cm)
Women	43"	(109 cm)
Teenagers	41"	(104 cm)
Small Children	35"	(89 cm)
Accessible	37"	(94 cm)

<sup>1</sup>Dry time and energy use testing performed by SGS International on standard ThinAir Hand Dryers to 0.25g or less of residual moisture, pursuant to the UL Environment Global Product Category Rules (PCR) for Hand Dryers.

<sup>2</sup>Based on testing performed by LMSTechnologies, 2023. <sup>3</sup>Exclusive digital image technology allows for the addition company, school or team looss with any color desion or a "oreen" message. <sup>5</sup>Secial Paint cowder-coated covers are available in many colors and textures.

